




EN3 SERIES OF EXTINGUISHERS

**RIGHT EXTINGUISHER TYPE
FOR THE RIGHT FIRE TYPE**

RE-ENGINEERED

**WORLD'S LARGEST
EN3 APPROVED RANGE**

**HIGHEST FIRE RATINGS
IN THE MARKET**

ADVANCED TECHNOLOGY

SFFECO.com

1kg ABC Powder
2kg ABC Powder
3kg ABC Powder
4kg ABC Powder
6kg ABC Powder
6kg ABC Powder High Performance
9kg ABC Powder
12kg ABC Powder
6kg ABC Powder Cartridge
9kg ABC Powder Cartridge

4kg BC Powder
6kg BC Powder
9kg BC Powder

3Ltr AFFF Foam
6Ltr AFFF Foam
6Ltr High Performance Foam
9Ltr AFFF Foam
6Ltr AFFF Foam Cartridge
9Ltr AFFF Foam Cartridge
6Ltr AFFF Foam Cartridge High Performance
9Ltr AFFF Foam Cartridge High Performance

6Ltr AR Foam
9Ltr AR Foam

6Ltr Water
9Ltr Water
9Ltr Water with Freeze Protected -20°C
9Ltr Water Cartridge

3Ltr Wet Chemical
6Ltr Wet Chemical

3Ltr Aqua Spray
6Ltr Aqua Spray

2kg CO2 Carbon Steel
5kg CO2 Carbon Steel

3L Water Mist
6Ltr Water Mist

THE

RANGE

**SFFECO**
firefix
EN3 SERIES OF EXTINGUISHERS



The new re-engineered SFFECO FireFix range of fire extinguishers is a revolutionary re-engineered product range manufactured strictly under ISO9001 processes, British Standards Institute (BSI) (BS EN3) and Pressure Equipment Directive (P.E.D / CE) approvals; ensuring you the absolute quality available in any market.

With more than 3 Decades of Excellence, it is only natural that SFFECO brings out this new highly engineered and largest range of extinguishers all EN3 approved and carrying the highest fire ratings. The SFFECO's Research and Development department knows and understands fire and the damage it can cause in mere seconds. That is why SFFECO has spent significant amount of time and money engineering and approving a product that WILL work when you need it and will do exactly the job that it is designed to do everytime (as long as it is maintained as per specifications).

No longer should the customer accept the one type fits all approach. Not just an extinguisher should be selected for the fire risk but the BEST type of extinguisher agent should be selected.



WH600SD

6 LTR WATER

WATER



firefix

SFFECO

EN3 SERIES OF EXTINGUISHERS

WATER extinguishes by cooling the fire and is the simple, conventional and ever-faithful extinguishing agent.



FEATURES

- EN3 Kitemark approval by BSI in the UK and CE marked
- Above average fire ratings offering maximum fire fighting ability with minimum size and weight
- Revolutionary new CE aluminum valve design
- Specially designed nozzle for best discharge application, accuracy and time
- Easy to use for untrained operator
- Easy to refill onsite
- Available in 6 & 9 Ltrs, Cartridge and Anti-freeze

INDUSTRIES

OFFICES ✓	STORAGE & ARCHIVE ✓	TIMBER INDUSTRY ✓	PAPER INDUSTRY ✓	RETAIL ✓
-----------	---------------------	-------------------	------------------	----------

a product of **SFFECO**



WH600SD

6 LTR WATER

SFFECO.com



13A FIRE RATING	WATER AGENT	6 LTR CAPACITY	NITROGEN PROPELLANT	+5°C - +60°C OPERATING TEMPERATURE
12 BAR WORKING PRESSURE	27 BAR TEST PRESSURE	36.0 SEC DISCHARGE TIME	>5.0 MTR RANGE OF THROW	PVC 10 520 MM HOSE TYPE AND LENGTH
534 MM HEIGHT	163 MM DIAMETER	9.8 KG FILLED WEIGHT	STEEL LOW-CARBON MATERIAL	

DECADES
of
EXCELLENCE

SAUDI FACTORY FOR FIRE EQUIPMENT
المصنع السعودي لأجهزة الإطفاء





WH900SD

9 LTR WATER

WATER



firefix

SFFECO

EN3 SERIES OF EXTINGUISHERS

WATER extinguishes by cooling the fire and is the simple, conventional and ever-faithful extinguishing agent.



FEATURES

- EN3 Kitemark approval by BSI in the UK and CE marked
- Above average fire ratings offering maximum fire fighting ability with minimum size and weight
- Revolutionary new CE aluminum valve design
- Specially designed nozzle for best discharge application, accuracy and time
- Easy to use for untrained operator
- Easy to refill onsite
- Available in 6 & 9 Ltrs, Cartridge and Anti-freeze

INDUSTRIES

OFFICES	STORAGE & ARCHIVE	TIMBER INDUSTRY	PAPER INDUSTRY	RETAIL
---------	-------------------	-----------------	----------------	--------

a product of **SFFECO**



WH900SD

9 LTR WATER

SFFECO.com



 21A FIRE RATING	 WATER AGENT	 9 LTR CAPACITY	 NITROGEN PROPELLANT	 +5°C - +60°C OPERATING TEMPERATURE
 12 BAR WORKING PRESSURE	 27 BAR TEST PRESSURE	 51.0 SEC DISCHARGE TIME	 >7.0 MTR RANGE OF THROW	 PVC 13 580 MM HOSE TYPE AND LENGTH
 586 MM HEIGHT	 183 MM DIAMETER	 13.5 KG FILLED WEIGHT	 STEEL LOW-CARBON MATERIAL	

DECADES
of
EXCELLENCE

SAUDI FACTORY FOR FIRE EQUIPMENT
المصنع السعودي لأجهزة الإطفاء





WH900FSD

9 LTR WATER-FREEZE PROTECTED
WATER WITH 35% FP MIX
FREEZE PROTECTED -20°C



WATER extinguishes by cooling the fire and is the simple, conventional and ever-faithful extinguishing agent.



FEATURES

- EN3 Kitemark approval by BSI in the UK and CE marked
- Suitable to operate to temperature -20°C without freezing
- Above average fire ratings offering maximum fire fighting ability with minimum size and weight
- Revolutionary new CE aluminum valve design
- Specially designed nozzle for best discharge application, accuracy and time
- Easy to use for untrained operator
- Easy to refill onsite
- Available in 6 & 9 Ltrs, Cartridge and Anti-freeze

INDUSTRIES

OFFICES	STORAGE & ARCHIVE	TIMBER INDUSTRY	PAPER INDUSTRY	RETAIL
---------	-------------------	-----------------	----------------	--------

a product of **SFFECO**



WH900FSD

9 LTR WATER | FREEZE PROTECTED -20°C

FREEZE PROTECTED
-20°C

SFFECO.com



 13A FIRE RATING	 WATER WITH 35% F.P. MIX AGENT	 9 LTR CAPACITY	 NITROGEN PROPELLANT	 -20°C - +60°C OPERATING TEMPERATURE
 12 BAR WORKING PRESSURE	 27 BAR TEST PRESSURE	 50.0 SEC DISCHARGE TIME	 >7.0 MTR RANGE OF THROW	 PVC 13 580 MM HOSE TYPE AND LENGTH
 586 MM HEIGHT	 183 MM DIAMETER	 13.5 KG FILLED WEIGHT	 STEEL LOW-CARBON MATERIAL	

DECADES
of
EXCELLENCE

SAUDI FACTORY FOR FIRE EQUIPMENT
المصنع السعودي لأجهزة الإطفاء





WH900CSD

9 LTR WATER - INSIDE CARTRIDGE
WATER
INSIDE CARTRIDGE



SFFECO
firefix
EN3 SERIES OF EXTINGUISHERS

WATER extinguishes by cooling the fire and is the simple, conventional and ever-faithful extinguishing agent.



FEATURES

- EN3 Kitemark approval by BSI in the UK and CE marked
- Above average fire ratings offering maximum fire fighting ability with minimum size and weight
- Revolutionary new CE aluminum valve design
- Specially designed nozzle for best discharge application, accuracy and time
- Easy to use for untrained operator
- Easy to refill onsite
- Available in 6 & 9 Ltrs, Cartridge and Anti-freeze

INDUSTRIES

OFFICES ✓	STORAGE & ARCHIVE ✓	TIMBER INDUSTRY ✓	PAPER INDUSTRY ✓	RETAIL ✓
-----------	---------------------	-------------------	------------------	----------

a product of **SFFECO**



WH900CSD

9 LTR WATER - INSIDE CARTRIDGE

INSIDE CARTRIDGE

SFFECO.com



21A FIRE RATING	WATER AGENT	9 LTR CAPACITY	CO₂ CARTRIDGE PROPELLANT	+5°C - +60°C OPERATING TEMPERATURE
12 BAR WORKING PRESSURE	27 BAR TEST PRESSURE	56.0 SEC DISCHARGE TIME	>7.0 MTR RANGE OF THROW	EPDM 13 583 MM HOSE TYPE AND LENGTH
610MM HEIGHT	183 MM DIAMETER	14.8 KG FILLED WEIGHT	STEEL LOW-CARBON MATERIAL	

DECADES
of
EXCELLENCE

SAUDI FACTORY FOR FIRE EQUIPMENT
المصنع السعودي لأجهزة الإطفاء



SAUDI FACTORY FOR FIRE EQUIPMENT reserves the right to make revisions to its products and their specifications, and to this catalogue and related information, without prior notice. All products must be installed and maintained in accordance with applicable instructions and/or standards.

SFFECO
GLOBAL
enterprise



SAUDI FACTORY FOR FIRE EQUIPMENT
المصنع السعودي للأجهزة الإطفاء

