



  
EN3 SERIES OF EXTINGUISHERS

**RIGHT EXTINGUISHER TYPE  
FOR THE RIGHT FIRE TYPE**

**RE-ENGINEERED**

**WORLD'S LARGEST  
EN3 APPROVED RANGE**

**HIGHEST FIRE RATINGS  
IN THE MARKET**

**ADVANCED TECHNOLOGY**

SFFECO.com

1kg ABC Powder  
2kg ABC Powder  
3kg ABC Powder  
4kg ABC Powder  
6kg ABC Powder  
6kg ABC Powder High Performance  
9kg ABC Powder  
12kg ABC Powder  
6kg ABC Powder Cartridge  
9kg ABC Powder Cartridge

4kg BC Powder  
6kg BC Powder  
9kg BC Powder

3Ltr AFFF Foam  
6Ltr AFFF Foam  
6Ltr High Performance Foam  
9Ltr AFFF Foam  
6Ltr AFFF Foam Cartridge  
9Ltr AFFF Foam Cartridge

6Ltr AFFF Foam Cartridge High Performance  
9Ltr AFFF Foam Cartridge High Performance

6Ltr AR Foam  
9Ltr AR Foam

6Ltr Water  
9Ltr Water  
9Ltr Water with Freeze Protected -20°C  
9Ltr Water Cartridge

3Ltr Wet Chemical  
6Ltr Wet Chemical

3Ltr Aqua Spray  
6Ltr Aqua Spray

2kg CO2 Carbon Steel  
5kg CO2 Carbon Steel

3L Water Mist  
6Ltr Water Mist

THE

RANGE

**SFFECO**  
firefix  
EN3 SERIES OF EXTINGUISHERS



The new re-engineered SFFECO FireFix range of fire extinguishers is a revolutionary re-engineered product range manufactured strictly under ISO9001 processes, British Standards Institute (BSI) (BS EN3) and Pressure Equipment Directive (P.E.D / CE) approvals; ensuring you the absolute quality available in any market.

With more than 3 Decades of Excellence, it is only natural that SFFECO brings out this new highly engineered and largest range of extinguishers all EN3 approved and carrying the highest fire ratings. The SFFECO's Research and Development department knows and understands fire and the damage it can cause in mere seconds. That is why SFFECO has spent significant amount of time and money engineering and approving a product that WILL work when you need it and will do exactly the job that it is designed to do everytime (as long as it is maintained as per specifications).



No longer should the customer accept the one type fits all approach. Not just an extinguisher should be selected for the fire risk but the BEST type of extinguisher agent should be selected.



# AS3D 3 LTR AQUA SPRAY 6% ADDITIVE



AQUA SPRAY is primarily a wetting agent with some foaming properties. It works by firstly applying a film to the fire which increases the area to which the water spreads, thereby providing excellent cooling properties.



## FEATURES

- EN3 Kitemark approval by BSI in the UK and CE marked
- High grade foam agent carrying strong chemical bond to form a strong film (bubbles) after Fire risks occurs
- Revolutionary new CE aluminum valve design
- Specially designed nozzle for best discharge application, accuracy and time
- More reliable and easier to control for an untrained user
- Safe for inadvertent use on electrical items upto 35kv.
- Suitable for use in a confined spaces
- Easy to Empty and refill onsite without mess or special filling machinery
- Available in 3 & 6 Ltrs

## INDUSTRIES



a product of **SFFECO**



# AS3D 3 LTR AQUA SPRAY

SFFECO.com



<b>Class E</b> upto 35 kV	<b>13A</b> FIRE RATING	<b>6%</b> ADDITIVE AGENT	<b>3 LTR</b> CAPACITY	<b>NITROGEN</b> PROPELLANT	<b>+5°C - +60°C</b> OPERATING TEMPERATURE
<b>12 BAR</b> WORKING PRESSURE	<b>27 BAR</b> TEST PRESSURE	<b>23.0 SEC</b> DISCHARGE TIME	<b>&gt;4.5 MTR</b> RANGE OF THROW	<b>PVC 10</b> <b>408 MM</b> HOSE TYPE AND LENGTH	
<b>428 MM</b> HEIGHT	<b>130 MM</b> DIAMETER	<b>5.1 KG</b> FILLED WEIGHT	<b>STEEL</b> <b>LOW-CARBON</b> MATERIAL		

DECADES  
of  
EXCELLENCE

SAUDI FACTORY FOR FIRE EQUIPMENT  
المصنع السعودي لأجهزة الإطفاء





# AS6D 6 LTR AQUA SPRAY 6% ADDITIVE



AQUA SPRAY is primarily a wetting agent with some foaming properties. It works by firstly applying a film to the fire which increases the area to which the water spreads, thereby providing excellent cooling properties.



## FEATURES

- EN3 Kitemark approval by BSI in the UK and CE marked
- High grade foam agent carrying strong chemical bond to form a strong film (bubbles) after Fire risks occurs
- Revolutionary new CE aluminum valve design
- Specially designed nozzle for best discharge application, accuracy and time
- More reliable and easier to control for an untrained user
- Safe for inadvertent use on electrical items upto 35kv.
- Suitable for use in a confined spaces
- Easy to Empty and refill onsite without mess or special filling machinery
- Available in 3 & 6 Ltrs

## INDUSTRIES



a product of **SFFECO**



# AS6D 6 LTR AQUA SPRAY

SFFECO.com



 Class E upto 35 kV	 <b>21A</b> FIRE RATING	 <b>6%</b> ADDITIVE AGENT	 <b>6 LTR</b> CAPACITY	 <b>N<sub>2</sub></b> NITROGEN PROPELLANT	 <b>+5°C - +60°C</b> OPERATING TEMPERATURE
 <b>12 BAR</b> WORKING PRESSURE	 <b>27 BAR</b> TEST PRESSURE	 <b>21.0 SEC</b> DISCHARGE TIME	>5.0 MTR Range of Throw icon"/> <b>&gt;5.0 MTR</b> RANGE OF THROW	 <b>PVC 10</b> <b>518 MM</b> HOSE TYPE AND LENGTH	
 <b>534 MM</b> HEIGHT	 <b>163 MM</b> DIAMETER	 <b>9.8 KG</b> FILLED WEIGHT	 <b>STEEL</b> LOW-CARBON MATERIAL		

DECADES  
of  
EXCELLENCE

SAUDI FACTORY FOR FIRE EQUIPMENT  
المصنع السعودي لأجهزة الإطفاء



SAUDI FACTORY FOR FIRE EQUIPMENT reserves the right to make revisions to its products and their specifications, and to this catalogue and related information, without prior notice. All products must be installed and maintained in accordance with applicable instructions and/or standards.

**SFFECO**  
**GLOBAL**  
enterprise



**SAUDI FACTORY FOR FIRE EQUIPMENT**  
**المصنع السعودي للأجهزة الإطفاء**

