SFFECO

firefix

EN3 SERIES OF EXTINGUISHERS

RIGHT EXTINGUISHER TYPE
FOR THE RIGHT FIRE TYPE

RE-ENGINEERED

WORLD'S LARGEST
EN3 APPROVED RANGE

HIGHEST FIRE RATINGS
IN THE MARKET

ADVANCED TECHNOLOGY

CE 1266

KM 60052

SFFECO.com

THE RANGE

1kg ABC Powder
2kg ABC Powder
3kg ABC Powder
4kg ABC Powder
6kg ABC Powder
6kg ABC Powder High Performance
9kg ABC Powder
12kg ABC Powder
6kg ABC Powder Cartridge
9kg ABC Powder Cartridge

4kg BC Powder
6kg BC Powder
9kg BC Powder

3Ltr AFFF Foam
6Ltr AFFF Foam
6Ltr High Performance Foam
9Ltr AFFF Foam
6Ltr AFFF Foam Cartridge
9Ltr AFFF Foam Cartridge
6Ltr AFFF Foam Cartridge High Performance
9Ltr AFFF Foam Cartridge High Performance

6Ltr A.R Foam
9Ltr A.R Foam

6Ltr Water
9Ltr Water
9Ltr Water with Freeze Protected -20°C
9Ltr Water Cartridge

3Ltr Wet Chemical
6Ltr Wet Chemical

3Ltr Aqua Spray
6Ltr Aqua Spray

2kg CO2 Carbon Steel
5kg CO2 Carbon Steel

3L Water Mist
6Ltr Water Mist

SFFECO

FireFix

EN3 SERIES OF EXTINGUISHERS

CE 1266

KM 60052

SFFECO®

The new re-engineered SFFECO FireFix range of fire extinguishers is a revolutionary re-engineered product range manufactured strictly under ISO9001 processes, British Standards Institute (BSI) (BS EN3) and Pressure Equipment Directive (P.E.D / CE) approvals; ensuring you the absolute quality available in any market.

With more than 3 Decades of Excellence, it is only natural that SFFECO brings out this new highly engineered and largest range of extinguishers all EN3 approved and carrying the highest fire ratings. The SFFECO's Research and Development department knows and understands fire and the damage it can cause in mere seconds. That is why SFFECO has spent significant amount of time and money engineering and approving a product that WILL work when you need it and will do exactly the job that it is designed to do everytime (as long as it is maintained as per specifications).

No longer should the customer accept the one type fits all approach. Not just an extinguisher should be selected for the fire risk but the BEST type of extinguisher agent should be selected.

CE 1266

CD2D
2 LTR CO_2
CARBON DIOXIDE

KM 60052

SFFECO firefix

EN3 SERIES OF EXTINGUISHERS

CARBON DIOXIDE being an inert gas works by expelling the oxygen and thereby suffocating the fire and is suitable for common industries where small class B or Electrical risks occur. It is always to be accompanied by a suitable extinguisher (Foam or Water) to cover class A risks.

FEATURES

- EN3 Kitemark approval by BSI in the UK and CE marked
- Suitable for Class B and Electrical Fires
- Leaves no residue when applied due to evaporation
- Safe for use on electrical items
- Available in 2 & 5 Kg

INDUSTRIES

OFFICES ✓ RETAIL ✓ RESTAURANTS ✓ HOTELS ✓ INDUSTRY ✓ ASSEMBLY POINTS ✓ LABORATORY ✓

a product of **SFFECO**

CD2D
2 KG CARBON DIOXIDE

SFFECO.com

Class E upto 35 kV — 34B FIRE RATING	CARBON DIOXIDE AGENT	2 KG CAPACITY	CO_2 CARBON DIOXIDE PROPELLANT	-20°C - +60°C OPERATING TEMPERATURE
150 BAR WORKING PRESSURE	250 BAR TEST PRESSURE	10.5 SEC DISCHARGE TIME	>2.5 MTR RANGE OF THROW	N/A HOSE TYPE AND LENGTH
515 MM HEIGHT	114 MM DIAMETER	7.2 KG FILLED WEIGHT	CARBON STEEL MATERIAL	

DECADES of EXCELLENCE

SAUDI FACTORY FOR FIRE EQUIPMENT

المصنع السعودي لأجهزة الإطفاء

SFFECO

CE 1266

CD5D
5 LTR CO_2
CARBON DIOXIDE

KM 60052

SFFECO fireFix

EN3 SERIES OF EXTINGUISHERS

CARBON DIOXIDE being an inert gas works by expelling the oxygen and thereby suffocating the fire and is suitable for common industries where small class B or Electrical risks occur. It is always to be accompanied by a suitable extinguisher (Foam or Water) to cover class A risks.

FEATURES

- EN3 Kitemark approval by BSI in the UK and CE marked
- Suitable for Class B and Electrical Fires
- Leaves no residue when applied due to evaporation
- Safe for use on electrical items
- Available in 2 & 5 Kg

INDUSTRIES

OFFICES ✓ RETAIL ✓ RESTAURANTS ✓ HOTELS ✓
INDUSTRY ✓ ASSEMBLY POINTS ✓ LABORATORY ✓

a product of **SFFECO**

CD5D
5 KG CARBON DIOXIDE

SFFECO.com

Class E upto 35 kV; 70B FIRE RATING	CARBON DIOXIDE AGENT	5 KG CAPACITY	CO_2 CARBON DIOXIDE PROPELLANT	-20°C - +60°C OPERATING TEMPERATURE
150 BAR WORKING PRESSURE	250 BAR TEST PRESSURE	12.0 SEC DISCHARGE TIME	>3.0 MTR RANGE OF THROW	PVC 17 EPDM 8 1100 MM HOSE TYPE AND LENGTH
665 MM HEIGHT	152 MM DIAMETER	17.1 KG FILLED WEIGHT	CARBON STEEL MATERIAL	

DECADES of EXCELLENCE

SAUDI FACTORY FOR FIRE EQUIPMENT
المصنع السعودي لأجهزة الإطفاء

SFFECO ®

SAUDI FACTORY FOR FIRE EQUIPMENT reserves the right to make revisions to its products and their specifications, and to this catalogue and related information, without prior notice. All products must be installed and maintained in accordance with applicable instructions and/or standards.

SFFECO GLOBAL enterprise

SFFECO®

SAUDI FACTORY FOR FIRE EQUIPMENT

المصنع السعودي لأجهزة الإطفاء